

# CLASSIC WARM DIM

Fixed


# ORLUNA®

Project Reference: \_\_\_\_\_

Product Reference: \_\_\_\_\_

## Luminaire Details

Fitting Type	Fixed Downlight
IP Rating	IP44 / IP65
Warranty	5 Years
Class	III
IP Zone	Zone 1
Standards	CE, BS EN 60598
Material	Aluminium ADC12
Cable type	2 Core 0.75mm <sup>2</sup>
Cable Length	300mm
Bezel Temp	F Rated



## Features & Benefits

- Halogen-style Warm Dimming
- TRUE BEAM
- High LOR

## 1800K - 2650K WARM DIM

LIGHT VALUES	MEDIUM	WIDE	FLOOD
<b>Beam Width FWHM</b>	<b>29°</b>	<b>44°</b>	<b>51°</b>
Initial Lumens*	901	901	901
Engine Lumens*	770	748	734
<small>*(Tc 85°C, +/-7%)</small>			
Engine Lm/W	63	61	60
Luminaire Cd	1498	924	809
Binning SDCM (Hot)	3		
DUV	0.001		
CRI (typ)(R9)	<b>94 (73)</b>		
TM30 Rf Rg	Rf 92 Rg 101		
Lifetime (ambient)	L70 B5 50,000hrs		

For full test data, see Luminaire Photometric Reports at [orluna.com/downloads](http://orluna.com/downloads)

## LUMINAIRE POWER

Voltage	36v
Drive Current	300mA
Circuit Power (typ)	12.2W

## DRIVER

Protocols	Mains Dim / DALI / 0-10V / Non-dim
Dim to Dark	0.1% Lux
Distance from product	20m (series wiring)
Emergency	Emergency packs available

## Specification Code

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	IP Rating
<b>WD</b>	<b>C</b>	<b>WD</b>	<b>M</b>	<b>M</b>	<b>W</b>	<b>F 44 E</b>
		WD / Warm Dim	M / Mains Dim D / DALI O / 0-10v X / No Driver	M / Medium W / Wide F / Flood	W / White RAL 9010 D / White RAL 9003 E / White RAL 9016 B / Black RAL 9005 F / Antique Brass G / Polished Brass J / Antique Bronze K / Brushed Chrome L / Polished Chrome H / Antique Copper I / Polished Copper C / Other RAL	F / Fire Rated 44 / IP44 65 / IP65 P / Sea & Spa E / Emergency Z / LSZH Cable

ORLUNA LED Technologies  
Unit C, Holly Industrial Park,  
Ryan Way, Watford  
Herts WD24 4YP

info@orluna.com

+44 (0) 1923 889 712

09/12/17