

CURVE WARM DIM

Tilt

ORLUNA®

Project Reference: _____


Product Reference: _____

Luminaire Details

Fitting Type	Tilt Downlight
IP Rating	IP44
Warranty	5 Years
Class	III
IP Zone	Zone 1
Standards	CE, BS EN 60598
Material	Aluminium ADC12
Cable type	2 Core 0.75mm ²
Cable Length	300mm
Bezel Temp	F Rated

Features & Benefits

- Curve blends into the ceiling
- 20° tilt with increased height shield
- Warm dimming from 3000K to 1800K
- 98CRI R9:99
- Trubeam: A smooth, defined beam



1800K - 3000K WARM DIM

LIGHT VALUES	MEDIUM	WIDE	FLOOD
Beam Width FWHM	32°	45°	47°
Initial Lumens*	1030	1030	1030
Engine Lumens*	882	873	876
<small>*(Tc 85°C, +/-7%)</small>			
Engine Lm/W	75	74	74
Luminaire Cd	1378	808	870
Binning SDCM (Hot)	3		
DUV	0.001		
CRI (typ)(R9)	98 (99)		
TM30 Rf Rg	Rf 94 Rg 101		
Lifetime (ambient)	L90 B5 50,000hrs		

For full test data, see Luminaire Photometric Reports at orluna.com/downloads

LUMINAIRE POWER

Voltage	34v
Drive Current	300mA
Circuit Power (typ)	11.8W

DRIVER

Protocols	Mains Dim / DALI / 0-10V / Non-dim
Dim to Dark	0.1% Lux
Distance from product	20m (series wiring)
Emergency	Emergency packs available

Specification Code

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	IP Rating
WD	CVT	WD	M	M	W	F 44 E
		WD / Warm Dim	M / Mains Dim D / DALI O / 0-10v X / No Driver	M / Medium W / Wide F / Flood	W / White RAL 9010 D / White RAL 9003 E / White RAL 9016 B / Black RAL 9005 C / Other RAL	F / Fire Rated 44 / IP44 J / Jigsaw E / 3hr Emergency Z / LSZH Cable

ORLUNA LED Technologies
Unit C, Holly Industrial Park,
Ryan Way, Watford
Herts WD24 4YP

info@orluna.com

+44 (0) 1923 889 712

03/08/19