

# FADE LOPRO

## Tilt & Rotate Twin


# ORLUNA®

Project Reference: \_\_\_\_\_

Product Reference: \_\_\_\_\_

### Luminaire Details

Fitting Type	Adjustable Downlight
IP Rating	IP54
Warranty	5 Years
Class	III
IP Zone	Zone 1
Standards	CE, BS EN 60598
Material	Aluminium ADC12
Cable type	2 Core 0.75mm <sup>2</sup>
Cable Length	300mm
Bezel Temp	F Rated



### Features & Benefits

- 98CRI R9 99
- Ultra low profile
- Low glare
- Plaster-in
- 360° rotate and tilt behind the scenes

	2700K LOPRO 98CRI				3000K LOPRO 98CRI			
LIGHT VALUES	NARROW	MEDIUM	WIDE	* All values are per light engine	NARROW	MEDIUM	WIDE	
Beam Width FWHM	19°	21°	34°		18°	20°	35°	
Initial Lumens*	1055	1055	1055		1057	1057	1057	
Engine Lumens*	791	799	814		827	813	832	
*(Tc 85°C, +/-7%)								
Engine Lm/W	68	69	70		71	70	72	
Luminaire Cd	3819	3028	1138		3835	3027	1105	
Binning SDCM (Hot)	2				2			
DUV	0.001				0.001			
CRI (typ)(R9)	98 (98)				98 (99)			
TM30 Rf Rg	Rf 94 Rg 100			Rf 94 Rg 101				
Lifetime (ambient)	L90 B5 50,000hrs			L90 B5 50,000hrs				

For full test data, see Luminaire Photometric Reports at [orluna.com/downloads](http://orluna.com/downloads)

LUMINAIRE POWER	2700K	3000K
Voltage	34v	34v
Drive Current	300mA	300mA
Circuit Power (typ)	11.6W	11.6W

DRIVER	Protocols	Mains Dim / DALI / 0-10V / Non-dim
Dim to Dark	0.1% Lux	
Distance from product	20m (series wiring)	
Emergency	Emergency packs available	

### Specification Code

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	Baffle Colour	Options
<b>LO</b>	<b>FD2</b>	<b>27</b>	<b>M</b>	<b>N</b>	<b>W</b>	<b>BB</b>	<b>F 54 E</b>
		27 / 2700K 30 / 3000K 40 / 4000K	M / Mains Dim D / DALI O / 0-10v N / Non Dim X / No Driver	N / Narrow M / Medium W / Wide	W / White RAL 9010 D / White RAL 9003 E / White RAL 9016 B / Black RAL 9005 F / Antique Brass G / Polished Brass J / Antique Bronze K / Brushed Chrome L / Polished Chrome H / Antique Copper I / Polished Copper C / Other RAL	BB / Black 9005 WB / White 9010 DB / White 9003 EB / White 9016 FB / Antique Brass GB / Gold Anodised JB / Antique Bronze KB / Brushed Chrome LB / Polished Chrome HB / Antique Copper IB / Polished Copper MB / Polished Brass CB / Other RAL	F / Fire Rated 54 / IP54 65 / IP65 (Gaiter) P / Sea & Spa T / Lockable Tilt & Rotate E / 3hr Emergency H / Honeycomb S / Spreader Lens N / Frosted Lens Z / LSZH Cable

ORLUNA LED Technologies  
Unit C, Holly Industrial Park,  
Ryan Way, Watford  
Herts WD24 4YP

info@orluna.com

+44 (0) 1923 889 712

03/13/19