

Orluna DIM1/DIM2

ORLUNA®

Control system compatibilty

Project Reference: _____

Product Reference: _____

Control System Details


Manufacturer Varilight
 Model VPRO (Custom)
 Load Range 0-200W
 Control Type Adaptive (Leading/Trailing)

Luminaire Details

Engine Origin
 Driver Osram OTe11
 Wattage 12.4W

Summary

Dims to 0.08%
 Minimum 1, maximum 10 lights
 Commissioning mode removed on Orluna modules



Power Setting	Dim %	Cd
(MAX) 12.4	100.00%	3998
11.8	95.80%	3830
11.0	86.00%	3438
10.0	81.77%	3269
9.0	68.27%	2730
8.0	47.12%	1884
7.0	39.81%	1592
6.0	34.21%	1368
5.0	29.00%	1160
4.0	27.41%	1096
3.5	23.52%	940
3.0	16.80%	672
2.5	14.93%	597
2.1	9.49%	379
1.8	6.42%	256
1.6	4.39%	176
1.5	1.92%	76.9
1.45	1.28%	51.0
1.4	0.56%	22.4
(MIN) 1.38	0.08%	3.1

Min. Luminaires 1
Max. Tested Luminaires 10
Max. Extrapolated Luminaires 10 (First Channel)
Waveform Smooth
Flicker None
Audible Noise None above ambient 32dB
Instant Switch-on at Min % 0.56% or 1.4W

Notes We recommend a custom VPRO provided by Orluna that removes commissioning mode. Commissioning mode can sometimes cause flickering and instability, and the removal of this mode ensures perfect performance.

Minimum Level



Maximum Level

